

door + window coverings



Venetian Blinds



Venetian Blinds

FOR DOORS + WINDOWS

Traditional metal slat venetian blinds offer timeless beauty. Select from a broad range of colored aluminum slats with contemporary surface textures and finishes for the perfect blinds for each room in your home.

Ideal for doors and windows, single and dual operation venetian blinds can be installed on tilt + turn doors and windows, swing doors, and picture windows. With various mounting options, the doors and windows can easily tilt or open even when the blinds are closed.



Single Operation/Mini

Single operation venetian blinds are fixed at the top and free-hanging at the bottom. They open and close with a variety of lifting systems: cord, chain, crank, and motorized.

Chain Operation

Easily raise and lower the blinds and tilt the slats with an elegant translucent bead chain. Attractive design created by a slat inserted in the top rail, color coordinated with the body of the blind.



Rod & Cord Operation

Tilt the slats with a clear rod and lift and lower the blinds with a cord.

Motorized Operation

For hard to reach windows or simply for additional convenience and luxury, blinds can be operated electrically. Select handheld remote controls or wall-mounted wired controls to suit your needs or lifestyle.

Dual Operation/TwinLine

Dual operation venetian blinds can easily move from the top down or from the bottom up. The slat angle is adjusted using a rotary wheel that is on the top handle or with a side guide (optional).

Design Options

Colors

The aluminum slats are available in 110 color choices to match any décor. Select from silk matt, high gloss, or wave finishes, in addition to solid, perforated, or slats with perforated edges.

Slats

Depending on the type of blind, slats are available in four different widths: 16mm, 25mm, 35mm and 50mm.

Mounting Frames

The mounting frames are available with your choice of a silver anodized or white powder-coated finish. Custom colors may be possible, upon request.

Mounting

Single operation models can be mounted to the ceiling (CM) or face mounted to the wall (FM). Ideal for large windows.

Dual operation models can be mounted between the glazing beads (BTB) or face mounted to the window or door (FM). Ideal for doors and tilt + turn windows.

Size Guide

Single Operation/Mini

	Model 09-1091 5/8 inch / 16 mm slats	Model 09-1191 1" inch / 25 mm slats
Minimum Width	13 in / 330 mm	13 in / 330 mm
Maximum Width	70-7/8 in / 1800 mm	102-3/8 in / 2600 mm
Maximum Height	118 in / 3000 mm	118 in / 3000 mm
Maximum Area	53-1/2 sq. ft. / 5 m ²	53-1/2 sq. ft. / 5 m ²

Dual Operation/TwinLine

	Model 09-7080 5/8 inch / 16 mm slats	Model 09-7180 1" inch / 25 mm slats
Minimum Width	13- 1/4 in / 336 mm	13- 1/4 in / 336 mm
Maximum Width	59 in / 1500 mm	59 in / 1500 mm
Maximum Height	98- 3/8 in / 2500 mm	98 in / 2500 mm
Maximum Area	17 sq. ft. / 1.6 m ²	21 1/2 sq. ft. / 2 m ²

PROUDLY DISTRIBUTED BY:

innotech
windows + doors

Learn more at www.innotech-windows.com

